

## **FUJINON**

型番	Product Name	Ver.2.0 CF50ZA-1S
焦点距離 [mm]	Focal length [mm]	50
	(design value)	(48.44)
絞り範囲 (F値)	Iris range (Fnumber)	F2.4-F16
画角 (H x V)	Angle of view	16.6° × 12.5° (1.1")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance	∞ - 200
	(from front of lens barrel) [mm]	
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	M37.5 x 0.5
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	155
適合センサーサイズ (標準)	Sensor size (std.)	1.1" (2.5μm)
バックフォーカス (空気換算長) [mm]	Back focal length (in air) [mm]	21.18
フランジバック [mm]	Flange back [mm]	17.526
入射瞳位置 (マウント面から) [mm]	Entrance pupil position	-26.73
	(from Mount) [mm]	
射出瞳位置 (結像面より) [mm]	Exit pupil position	-99.72
	(from image plane) [mm]	
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-2.49
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	-30.92
主点間隔 [mm]	Distance between the principal points [mm]	-28.43
TVディストーション [%]	TV distortion [%]	-0.17
外形寸法 [mm]	Dimension [mm]	φ39 × 68.0
主光線入射角度 [°]	Chief Ray Angle [°]	4.84
周辺光量比 (F4.0·対角端) [%]	Relative illumination [%]	94
	(Aperture: F4.0,	
	Image height : at diagonal)	
周辺光量比 (開放・対角端) [%]	Relative illumination [%]	58
	(Aperture: at full open,	
	Image height : at diagonal)	
	Operation Temperature	-10℃ ~ +50℃
These energianties are subject to share	•	10 May 10

These specifications are subject to change without notice.

10-May-19